



EE820



**Motion detector Infrared 140°, IP55, wall mounted, white**

**Technical properties**

**Architecture**

Bus system Without

**Functions**

Function can only be used as individual unit

**Main electrical features**

Rated operational voltage Ue 230 V

Frequency 50/60 Hz

**Dimensions**

Height of installed product 2.5 m

Recommended installation height 2.5 m

**Power supply**

Supply voltage 230 V +10% / -15%

**Detection**

Detection angle 140 °

Frontal detecting distance 16 m

Side detecting distance 8 m

**Materials**

Colour white

RAL colour RAL 9010 - Pure white

Material plastic

**Lighting control**

Response brightness, adjustable ≈ 5...1000 lx

Brightness measurement range 5 / 1000 Lux

**LED control**

LED with LED detection and mode indicator

**Installation, mounting**

Maximum Mounting Height 4 m

Installation mode for wall and ceiling mounting, corner installation with adapter

**Connection**

Type of connection with plug-in terminals

**Settings**

---

Response value sensitivity adjustable	No
---------------------------------------	----

---

Delay time, adjustable	5 s...15 mn
------------------------	-------------

---

Setting	with potentiometers for setting the response brightness and delay time without dismantling
---------	--

**Scope of delivery**

---

Component	with fitting material
-----------	-----------------------

**Equipment**

---

Angle of horizontal detection	140 °
-------------------------------	-------

---

Slewing	horizontally rotatable
---------	------------------------

**Safety**

---

REACH conform	Yes
---------------	-----

---

RoHS conform	Yes
--------------	-----

**Use conditions**

---

Operating temperature	-20...55 °C
-----------------------	-------------

---

Energy-saving	low intrinsic energy requirement ; energy saving by means of presence and brightness-dependent ON and OFF switching of light
---------------	--