



EE840



Motion detector 360° white

Technical properties

Architecture

Fixing mode	surface-mounting
-------------	------------------

Main electrical features

Frequency	50/60 Hz
-----------	----------

Dimensions

Height of installed product	2.5 m
Recommended installation height	2.5 m

Power supply

Supply voltage	230 V +10% / -15%
----------------	-------------------

Detection

Detection angle	360 °
Detection angle	360 °
Detection field Ø, on floor	≈ 12 m
Frontal detecting distance	12 m
Side detecting distance	6 m

Materials

Colour	white
RAL colour	RAL 9010 - Pure white
Material	plastic

Lighting control

Response brightness, adjustable	≈ 5...1000 lx
Brightness measurement range	5 / 1000 Lux

Installation, mounting

Maximum Mounting Height	2.5 m
-------------------------	-------

Connection

Type of connection	with screw terminals
--------------------	----------------------

Settings

Response value sensitivity adjustable	Yes
Response sensitivity, settable	20...100 %
Delay time, adjustable	5 s...15 mn

Setting with potentiometers for fine adjustment of the response brightness, sensitivity and delay time

Scope of delivery

Component	with fitting material
-----------	-----------------------

Equipment

Angle of horizontal detection	360 °
-------------------------------	-------

Slewing	vertically slewing
---------	--------------------

Safety

Protection index IP	IP55
---------------------	------

REACH conform	Yes
---------------	-----

RoHS conform	Yes
--------------	-----

Use conditions

Operating temperature	-20...55 °C
-----------------------	-------------

Energy-saving	low intrinsic energy requirement
---------------	----------------------------------