



HFD325

**Fuse comb. switch 3P - 250 A / T1**

**Technical properties**

**Architecture**

Type of order	Door coupling rotary drive
Number of poles	3 P
Type of pole	3 P

**Main electrical features**

Rated operational voltage Ue	380 / 415 V
Rated current	250 A

**Voltage**

Rated insulation voltage	750 V
--------------------------	-------

**Electric current**

Short-circuit current with gI-gG fuses	100 kA
Rating current of fuse cartridge	50 / 63 / 80 / 100 / 125 / 160 / 200 / 224 / 250 A

**Fuse**

CharactFuse	gI ; gG
Fuse Size	NH1

**Dimensions**

Depth of installed product	146 mm
Height of installed product	195 mm
Width of installed product	234 mm

**Power**

Total power loss under IN	123.3 W
Power loss per pole at In	41.1 W
Contact rating with 400 V in AC1	164 kW

**Cover, door**

Interlockable	Yes
---------------	-----

**Materials**

Toggle colour	Grey
---------------	------

**Installation, mounting**

Suitable for busbar mounting	No
Suitable for front mounting center	No
Suitable for front mounting	No
Suitable for ground mounting	Yes

**Connection**

Type of connection	with screw
--------------------	------------

**Cable**

Length of conductors used for the heating test (m) according to product standard	2 m
--	-----

Conductor cross-section used for heating test(mm <sup>2</sup> ) according to product standard	150 mm <sup>2</sup>
---	---------------------

**Equipment**

Number of auxiliary contacts as normally closed contact	0
---	---

Number of auxiliary contacts as normally open contact	0
---	---

Number of auxiliary contacts as change-over contact	0
---	---

Can be accessorized	Yes
---------------------	-----

**Standards**

Standard text	IEC 60947-3
---------------	-------------

European directive RoHs	voluntary compliance
-------------------------	----------------------

**Safety**

REACH conform	Yes
---------------	-----

RoHS conform	Yes
--------------	-----

Halogen free	No
--------------	----

**temperatur**

Ambient air temperature during heating test according to the product standard	24 °C
---	-------

Max. admissible temperature on accessible parts (intended to be touched)	80 °C
--	-------

Max. admissible temperature on accessible parts (manual operating means)	65 °C
--	-------

Max. admissible temperature on access. parts (not touched for normal operation)	90 °C
---	-------

Max. admissible temperature on terminals	110 °C
--	--------

Temp.-rise limits for access. parts (toggle) according to product standard	25 K
--	------

Temp.-rise limits for access. parts (not touched) according to product standard	50 K
---	------

Temp.rise limits for access. parts (to be touched) according to product standard	40 K
--	------

Temperature-rise limits for terminals according to the product standard	70 K
---	------

Temperature-rise measured on accessible parts at In (manual operating means)	25 K
--	------

Temperature-rise measured on access. parts at In (not touched normal operation)	50 K
---	------

Temperature-rise measured on accessible parts at In (intended to be touched)	40 K
--	------

Temperature-rise measured on terminals at In	70 K
--	------