



TX511

**EIB presence detector with Light Regulation**

**Technical properties**

**Architecture**

|            |     |
|------------|-----|
| Bus system | KNX |
|------------|-----|

**Functions**

|                    |       |
|--------------------|-------|
| Max. temporisation | 30 mn |
|--------------------|-------|

**Connectivity**

|                         |   |
|-------------------------|---|
| Number of binary inputs | 0 |
|-------------------------|---|

**Measurement**

|                  |          |
|------------------|----------|
| Detection Method | presence |
|------------------|----------|

**Detection**

|                             |      |
|-----------------------------|------|
| Angle of vertical detection | 55 ° |
| Frontal detecting distance  | 7 m  |
| Side detecting distance     | 6 m  |

**Materials**

|                           |                       |
|---------------------------|-----------------------|
| RAL colour                | RAL 9010 - Pure white |
| Material                  | plastic               |
| Type of surface treatment | Other                 |

**Installation, mounting**

|                         |     |
|-------------------------|-----|
| Maximum Mounting Height | 4 m |
|-------------------------|-----|

**Settings**

|                    |      |
|--------------------|------|
| Min. temporisation | 1 mn |
|--------------------|------|

**Scope of delivery**

|                         |     |
|-------------------------|-----|
| Bus connection included | Yes |
|-------------------------|-----|

**Equipment**

|                               |       |
|-------------------------------|-------|
| Substation input              | Yes   |
| Number of channels            | 1     |
| Bidirectional radio frequency | No    |
| Angle of horizontal detection | 360 ° |