




TXB344



Binary input 4 fold + LED output 4 fold, flush mounted, KNX

Technical properties

Architecture

Fixing mode	flush-mounting
-------------	----------------

Functions

Bus module detachable	No
-----------------------	----

Compatibility

Extension unit	extension unit for light scene push-button
----------------	--

Controls and indicators

Button / push-button	with programming button and red programming LED
----------------------	---

Connectivity

Binary inputs	with 4 independent binary inputs for potential-free contacts
---------------	--

Voltage

Input voltage	5 V
Operating voltage over bus	21...32 V DC
System supply voltage	30V DC via bus

Electric current

Number of entry circuits	4
Intensity by input	0.85 mA

Dimensions

Dimensions (LLxwwxhh)	38 x 35 x 12 mm
Width of rail mounted device (RMD)	0 modules

Length

Max distance to switches	5 mm
--------------------------	------

Measurement

Input scanning voltage	per channel 5 V
------------------------	-----------------

Materials

Colour	stone grey
Material	Polyamid (PA)

Installation, mounting

Installation mode	for flush-mounted and hollow-wall mounting
-------------------	--

Connection

Conductor cross-section (flexible)	0.75...2.5 mm²
Conductor cross-section (rigid)	0.75...2.5 mm²
Connection to	Potential free, switch, push button, automation system
Bus coupling unit	with integral bus coupling unit
Type of connection	with pre-assembled cable
Bus connection	bus connection via connecting terminal
Cable	
Cable length extendable to	max. 5 m
Settings	
Supported configuration modes	system, easy
Scope of delivery	
Bus connection included	Yes
Use	
Differentiation characteristic 3 - Sales	with integral bus coupling unit
Safety	
Protection index IP	IP20
REACH conform	No
RoHS conform	Yes
Halogen free	No
Use conditions	
Operating temperature	0...45 °C
Storage/transport temperature	-20...70 °C
Identification	
Main design line	KNX