




TYA604B



quickconnect

Output module 4x 10A /230V~, KNX

Technical properties

Connectivity

| | |
|---------------------------|-----|
| With bus system KNX | Yes |
| With bus system KNX radio | No |

Settings

| | |
|------------------------------|-----|
| Supported configuration mode | ETS |
|------------------------------|-----|

Dimensions

| | |
|-----------------------|---|
| Number of width units | 4 |
|-----------------------|---|

Materials

| | |
|--------|------------|
| Colour | Light grey |
|--------|------------|

Equipment

| | |
|-------------------------------|-----|
| Radio frequency bidirectional | No |
| With switch for manual switch | Yes |

Electric current

| | |
|------------------------------------|------|
| Rated current | 10 A |
| Bus current consumption while idle | 3 mA |

Frequency

| | |
|-----------|------------|
| Frequency | 50 - 60 Hz |
|-----------|------------|

Power

| | |
|-------------------------------|---------------|
| Power incandescent lamp 230 V | 1200 - 1200 W |
| Output power | 1200 W |

Voltage

| | |
|------------------------------|-----------------|
| Rated operational voltage Ue | 230 - 230 V |
| System supply voltage | 30 V DC Via bus |

Safety

| | |
|-------------------------------|------|
| Ingress Protection (IP) class | IP20 |
|-------------------------------|------|

Use conditions

| | |
|-----------------------|------------|
| Operating temperature | -5 - 45 °C |
|-----------------------|------------|

Texts

| | |
|--------------------|---|
| Function | With safety functions e.g. for wind, rain, alarm, With positioning function for blind and lamella position, With sun shade function |
| Type of connection | With quickconnect plug-in terminals |

