



16286076

Rocker imprinted symbol for bell, lab. field, lens, Q.x, ant. velvety, lacq.

## Technical properties

### Controls and indicators

Push-buttons	also for KNX applications: push-button, 1gang, and group push-button, 1gang
Rocker switch/rocker push-button	for change-over/intermediate switch ; for rocker push-buttons

### Materials

Colour of design line	anthracite
Colour	anthracite
Material / workmanship	lacquered
Material	duroplastic

### Installation, mounting

Installation mode	clamp fastening
-------------------	-----------------

### Use cases

Application	Light control
-------------	---------------

### Use

Differentiation characteristic 1 - Sales	with labelling field
Differentiation characteristic 2 - Sales	Lens

### Safety

REACH conform	Yes
RoHS conform	Yes

### Identification

Application, usage	Light control ; Flush-mounted wet-room installation ; KNX - operating systems
Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1 ; Berker Q.3 ; Berker Q.7 ; Berker Q.9

### Instructions

Special note text	The IP44 degree of protection can only be achieved in conjunction with the appropriate neon, incandescent or LED lamp unit, as well as a sealing set for switches/push-buttons.
Information text	For labelling with names, notes etc. Labelling field height designed for 6 mm P-touch strip.