


5...30 °C



20266086

Thermostat, c	change-over	contact,	centre	plate,	Q.x,	ant.	velvety,	lacq.
---------------	-------------	----------	--------	--------	------	------	----------	-------

Technical properties

Technical properties	
Functions	
With cooling function	No
Main electrical features	
Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Electric current	
Switching current "Heating" at $\cos \phi = 0.6$	4 A
Heating switching current	10 A
"Switching current ""Cooling"" at $\cos \phi = 0.6$ "	2 A
"Switching current ""Cooling"""	5 A
Measurement	
Range of temperatures	5 / 30 °C
Materials	
Colour of design line	anthracite
Colour	anthracite
Material / workmanship	lacquered
Material	Plastic/metal
Installation, mounting	
Installation mode	without spreader claws
Connection	
Type of connection	with plug-in terminals
Equipment	
Switching temperature difference	≈ 0.5 K
Heating	for heating or cooling mode
Control	setting knob with temperature range limitation
Valve drives	e.g. for valve drives closed in de-energised state
Use conditions	
Energy efficiency class	I (1%)
temperatur	

Temperature

Identification			
Application, usage	HVAC control		
Main design line	Berker Q.1/Q.3/Q.7/Q.9		

Berker Q.1; Berker Q.3; Berker Q.7; Berker Q.9

Secondary design line(s)