



Rot. dimmer centre plate (R, L, C), soft-lock, 1930/glass, black glossy

Technical properties

Type of control unit	Push & rotativ
Functions	
Soft startup	bulb-preserving soft startu
Main electrical features	
Nominal voltage	230 \
Voltage	
Operating voltage	230 V A
Voltage	voltage test possible without dismantling
Fuse	
Fuse	short-circuit and overload proof (electronic fuse
Dimensions	
Axis dimension Ø	4 mn
Power	
Dimmable conventional transformers	50420 V/
connected load	50420 W/V/
Loss power at full load	≈ 5 V
Electronic transformers	50420 V
Measurement	
Extension unit input	with input for extension units insert for universa rotary dimme
Materials	
Colour of design line	blac
Colour	blac
Material	Plastic/meta
Incandescent bulbs control	
230 V incandescent lamps and halogen lamps	50420 V
Installation, mounting	
Installation mode	for screw fastening
Connection	
Type of load	universa

Type of connection	with plug-in terminals
Scope of delivery	
Component	with incremental encoder
Equipment	
Dimming principle	phase cut-on or cut-off according to load type, self- learning
low noise	very low noise
Brightness	with brightness memory
Use	
Differentiation characteristic 3 - Sales	Soft-lock
Use conditions	
Operating temperature	525 °C
Identification	
Release issue	2
Main design line	Serie 1930/Glas
Secondary design line(s)	Serie 1930, Serie 1930 Porzellan Made by Rosenthal, Serie Glass, Series R.classic
Instructions	
Information text	Trouble-free operation will be obtained only with Berker Tronic® transformers.