



41092045

**SCHUKO soc.out. LEDorient.,enhncd contact prot.,screw-in lift term.,R.cl,bl.**

### Technical properties

#### Architecture

Design according to DIN 49440

#### Configuration

Number of modules 1

#### Main electrical features

Nominal voltage 250 V

Rated voltage 250 V AC

Frequency 50/60 Hz

Rated current 16 A

#### Electric current

Rated current 16 A

#### Dimensions

Insertion depth 32 mm

#### Power

Power consumption 0.25 W/0.35 VA

#### Cover, door

Cover Central cover plate

#### Detection

Sensor integrated brightness sensor that switches the orientation light on at twilight and off when there is sufficient brightness

#### Materials

Colour of labelling 217,217,217

Colour of design line black

Material for printing PC-PMA black

Surface appearance glossy

#### Lighting control

Switch-off brightness  $\approx$  4 lx

Switch-on brightness  $\approx$  2 lx

Light intensity (white) 0.2 cd

#### LED control

LED white LED light ; long service life of the LED

**Installation, mounting**

Installation mode with spreader claws

**Connection**

Conductor cross-section (rigid) max. 2.5 mm<sup>2</sup>

Connection terminals according to IEC 60884-1

Connection terminals according to VDE 0620-1

Type of connection with screw-in lift terminals

**Cable**

Wiring through-wiring possible, therefore also ideal for retrofitting

**Settings**

Shading parameter R1\_czarny

Laser parameter R1\_schwarz

**Equipment**

Type of configuration Laserdruck

Lighting additional benefit by combination of a socket outlet with an orientation light

**Use**

Differentiation characteristic 2 - Sales enhanced contact protection

Differentiation characteristic 3 - Sales Screw-in lift terminals

**Safety**

REACH conform Yes

RoHS conform Yes

Halogen free Yes

Protection Enhanced contact protection

With enhanced contact protection Yes

**Identification**

Main design line Serie R.classic

**Instructions**

Special note text Note: When integrating this product into the Serie 1930, the 1gang frame for centre plate Ø 58 mm, order no.: 1382 0... may only be used. Installation in multiple combinations of the Serie 1930 is not possible!

Information text Caution! Items with special flush-mounted insert. Centre plates with LED orientation lights are not compatible with the standard socket outlets.