



5031

## Rocker push-button NO contact Module insert

### Technical properties

#### Architecture

Type of control unit rocker

#### Functions

Switching angle 3.5 °

#### Configuration

Switch mode Normally open contact

#### Compatibility

IFTTT support available No

#### Main electrical features

Nominal voltage 250 V

Rated voltage 250 V AC

Frequency 50/60 Hz

#### Electric current

Momentary-contact current 10 A

#### Dimensions

Depth 41.6 mm

Insertion depth 30 mm

Contact spacing > 3 mm

Height 70.8 mm

Width 70.8 mm

#### Installation, mounting

Installation mode with spreader claws

#### Connection

Conductor cross-section (rigid) max. 2.5 mm<sup>2</sup>

Connection terminals according to IEC 60669-1

Connection terminals according to VDE 0632-1

Type of connection with plug-in terminals

#### Scope of delivery

With lamp No

#### Equipment

Quantity of NC contacts 0

Quantity of NO contacts	1
Lighting	for lighting and monitoring circuit
<b>Use cases</b>	
Application	Barrier-free application ; HVAC-control ; Light control
<b>Identification</b>	
Application, usage	Light control
Main design line	Light control
<b>Instructions</b>	
Information text	spreader claws, insulated to the supporting ring, self-resetting