



5035

## Series push-button 2 NO contacts with common input terminal

### Technical properties

#### Architecture

Type of control unit	double rocker
----------------------	---------------

#### Functions

Switching angle	3.5 °
-----------------	-------

#### Configuration

Antibacterial treatment	No
-------------------------	----

#### Compatibility

IFTTT support available	No
-------------------------	----

#### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC

#### Electric current

Momentary-contact current	10 A
---------------------------	------

#### Dimensions

Depth	41.6 mm
Insertion depth	32.3 mm
Height	70.8 mm
Width	70.8 mm

#### Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

#### Connection

Connection terminals	according to IEC 60669-1
Connection terminals	according to VDE 0632-1

#### Scope of delivery

With lamp	No
-----------	----

#### Equipment

Quantity of NC contacts	1
Quantity of NO contacts	1

#### Use cases

Application	Light control
-------------	---------------

<b>Safety</b>	
Protection index IP	IP20
REACH conform	Yes
RoHS conform	Yes
Halogen free	Yes
<b>Identification</b>	
Application, usage	Light control
Main design line	Light control
<b>Instructions</b>	
Information text	spreader claws, insulated to the supporting ring, self-resetting