



75141165

IP20



Touch sensor 1gang comf, intg bus coupling unit, KNX - R.1, glass black

Technical properties

Functions

With room temperature controller Yes

Function for switch, push-button, dimmer and shutter functions ; Blocking function for sensor surface e.g. for cleaning the glass surface

Compatibility

Extension unit extension unit for light scene push-button

Controls and indicators

With LED indication Yes

Number of buttons 0

Operation operation by gently touching the sensor surfaces on the white LED

Dimensions

Depth 23 mm

Height 152 mm

Width 81 mm

Power

Current consumption 12.5 mA

Measurement

Value transmitter value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

Screen

With display Yes

Materials

Colour of labelling 217,217,217

Colour of design line glass black

Colour black

Surface appearance glossy

LED control

LED with blue operation LED and 2 white status LEDs

Installation, mounting

Installation mode for vertical mounting

Connection

Bus coupling unit	with integral bus coupling unit
Bus connection	bus connection via connecting terminal
Scope of delivery	
Bus connection included	Yes
Accessories included	
Matching products	for additional products to complement the installation in matching colours/materials, refer to the Design platform R.1/R.3 ; for suitable frames in the same "style" for additional applications, see the Design line R.x
Equipment	
Number of actuation points	2
With anti-theft/dismantling protection	Yes
Type of configuration	Laserdruck
Use	
Differentiation characteristic 3 - Sales	with integral bus coupling unit
Safety	
REACH conform	Yes
RoHS conform	Yes
Use conditions	
Operating temperature	-5...45 °C
Temperature	temperature measurement via internal temperature sensor or external communication object ; integrated temperature sensor for operation as controller extension unit ; additional connection for external temperature sensor
Identification	
Application, usage	KNX - operating systems
Main design line	KNX - Berker R.1 - configured
Secondary design line(s)	KNX ; Berker R.1