



75141860



Touch sensor 1 gang comf, intg bus coupling unit, KNX - R.1, glass p. white

Technical properties

		_	
 			-
	าตา		ns

Yes
for switch, push-button, dimmer and shutter func- tions; Blocking function for sensor surface e.g. for cleaning the glass surface
extension unit for light scene push-button
Yes
0
operation by gently touching the sensor surfaces on the white LED
23 mm
152 mm
81 mm
12.5 mA
value transmitter for dimming, position, brightness and temperature values 1 and 2 byte
Yes
glass polar white
white
RAL 9010 - Pure white
glossy
with blue operation LED and 2 white status LEDs
for vertical mounting

Connection

Bus coupling unit	with integral bus coupling unit
Bus connection	bus connection via connecting terminal
Scope of delivery	
Bus connection included	Yes
Accessories included	
Matching products	for additional products to complement the installa- tion in matching colours/materials, refer to the Design platform R.1/R.3; for suitable frames in the same "style" for additional applications, see the Design line R.x
Equipment	
Number of actuation points	2
With anti-theft/dismantling protection	Yes
Use	
Differentiation characteristic 3 - Sales	with integral bus coupling unit
Safety	
REACH conform	Yes
RoHS conform	Yes
Use conditions	
Operating temperature	-545 °C
Temperature	temperature measurement via internal temperature sensor or external communication object; integrated temperature sensor for operation as controller extension unit; additional connection for external temperature sensor
Identification	
Application, usage	KNX - operating systems
Main design line	KNX - Berker R.1
Secondary design line(s)	KNX ; Berker R.1