


system











Technical properties	
Architecture	
Fixing mode	flush-mounting
Functions	
With room temperature controller	No
Function	for switch, push-button, dimmer and shutter functions
Light scenes	retrieval, adjustment and storage of 8 light scenes
Compatibility	
Extension unit	extension unit for light scene push-button
Controls and indicators	
With LED indication	Yes
Number of buttons	2
Operation	one push-button operation for switching, pushing, shutters and dimming
Dimensions	
Labelling field length (W x H)	56.4 x 26.8 mm
Height	71 mm
Width	71 mm
Measurement	
Value transmitter	value transmitter for dimming, position, brightness and temperature values 1 and 2 byte
Screen	
With display	No
Materials	
Colour of labelling	217,217,217
Colour of design line	anthracite
Colour	anthracite
Material for printing	Paper
Type of surface treatment	Painted
Material family	Plastic
LED control	
LED	with white operation LED and 4 amber status LEDs
Settings	

Supported configuration modes

Scope of delivery

Bus connection included Yes

Equipment

Number of actuation points	4
With anti-theft/dismantling protection	Yes
Type of configuration	Beschriftungsfeld(er) - Folie
Product type:	product type: push-button 2gang
Controller extension unit	usable as thermostat extension unit

Use

Differentiation characteristic 1 - Sales with labelling fields

Differentiation characteristic 3 - Sales with integral bus coupling unit

Safety

Protection index IP	IP20
Protection	with dismantling protection

Use conditions

Operating temperature -5...45 °C

Identification

Application, usage	KNX - operating systems
Product family	product family: push-button
	KNX ; Berker Q.1 ; Berker Q.3 ; Berker Q.7 ; Berker
Secondary design line(s)	Q.9

Instructions

Labelling field sheet, order no. 9498 30 02, available Information text separately.