



75142830



KNX glass sensor 2gang comf, intg bus coupl. unit, KNX-TS sensor, glass p.white

Technical properties

Architecture

Fixing mode flush-mounting

Functions

With room temperature controller Yes

Function for switch, push-button, dimmer and shutter functions ; Blocking function for sensor surface e.g. for cleaning the glass surface

Compatibility

Extension unit extension unit for light scene push-button

Controls and indicators

With LED indication Yes

Number of buttons 0

Operation operation by gently touching the sensor surfaces on the white LED

Dimensions

Depth 37.7 mm

Depth 5.7 mm

Dimensions (W x H x D) 86 x 160 x 5.7 mm

Height 160 mm

Width 86 mm

Power

Current consumption 12.5 mA

Measurement

Value transmitter value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

Screen

With display No

Materials

Colour of design line glass polar white

Colour polarwhite

RAL colour RAL 9010 - Pure white

Material glass

Surface appearance glossy/matt

Type of surface treatment Tampography

LED control

LED with blue operation LED and 4 white status LEDs

Installation, mounting

Installation mode for vertical mounting

Connection

Bus coupling unit with integral bus coupling unit

Bus connection bus connection via connecting terminal

Scope of delivery

Bus connection included Yes

Accessories included

Matching products for glass frames in the same "style" for additional applications, see the Design line B.7 ; for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x

Equipment

Number of actuation points 4

With anti-theft/dismantling protection Yes

Use

Differentiation characteristic 3 - Sales with integral bus coupling unit

Use conditions

Operating temperature -5...45 °C

Temperature temperature measurement via internal temperature sensor or external communication object ; integrated temperature sensor for operation as controller extension unit ; additional connection for external temperature sensor

Identification

Application, usage KNX - operating systems

Main design line KNX - Berker TS Sensor

Secondary design line(s) KNX ; Berker TS Sensor

Instructions

Information text Only suitable for KNX.