



75142855



Touch sensor, 2-gang comf, intg bus coupling unit, KNX - R.3, glass black

Technical properties

With room temperature controller	Yes
Function	for switch, push-button, dimmer and shutter func- tions ; Blocking function for sensor surface e.g. for cleaning the glass surface
Compatibility	
Extension unit	extension unit for light scene push-button

With LED indication	Yes
Number of buttons	0
Operation	operation by gently touching the sensor surfaces on the white LED

Dimensions	
Depth	23 mm
Height	152 mm
Width	81 mm

Power	
Current consumption	12.5 mA

Current consumption	12.5 m/
Measurement	
Value transmitter	value transmitter for dimming, position, brightness and temperature values 1 and 2 byte
Screen	
With display	No
Materials	
Colour of design line	glass black
Colour	black

Materials	
Colour of design line	glass black
Colour	black
Surface appearance	glossy
LED control	

LED	with blue operation LED and 4 white status LEDs
Installation, mounting	

Installation mode	for vertical mounting

Connection	
Bus coupling unit	with integral bus coupling unit

Bus connection	bus connection via connecting terminal
Scope of delivery	
Bus connection included	Yes
Accessories included	
Matching products	for additional products to complement the installation in matching colours/materials, refer to the Design platform R.1/R.3; for suitable frames in the same "style" for additional applications, see the Design line R.x
Equipment	
Number of actuation points	4
With anti-theft/dismantling protection	Yes
Type of configuration	Laserdruck
Use	
Differentiation characteristic 3 - Sales	with integral bus coupling unit
Safety	
REACH conform	Yes
RoHS conform	Yes
Use conditions	
Operating temperature	-545 °C
	temperature measurement via internal temperature sensor or external communication object; integ- rated temperature sensor for operation as controller extension unit; additional connection for external
Temperature	temperature sensor
Identification	
Application, usage	KNX - operating systems
Main design line	KNX - Berker R.3
Secondary design line(s)	KNX ; Berker R.3