


75143326



IP20



## Technical properties

### Functions

With room temperature controller	No
Function	for switch, push-button, dimmer and shutter functions
Light scenes	retrieval, adjustment and storage of 8 light scenes

### Compatibility

Extension unit	extension unit for light scene push-button
----------------	--

### Controls and indicators

With LED indication	Yes
Number of buttons	3
Operation	one push-button operation for switching, pushing, shutters and dimming

### Dimensions

Labelling field length (W x H)	56.4 x 17 mm
Height	71 mm
Width	71 mm

### Measurement

Value transmitter	value transmitter for dimming, position, brightness and temperature values 1 and 2 byte
-------------------	---

### Screen

With display	No
--------------	----

### Materials

Colour of labelling	217,217,217
Colour of design line	anthracite
Material for printing	Paper
Surface appearance	velvety
Material family	Plastic

### LED control

LED	with white operation LED and 6 amber status LEDs
-----	--

### Settings

Supported configuration modes	system
Parameterisation	single and two push-button operation parameterisable

### Scope of delivery

Bus connection included Yes

### Equipment

Number of actuation points	6
With anti-theft/dismantling protection	Yes
Type of configuration	Beschriftungsfeld(er) - Folie
Product type:	product type: push-button 3gang
Controller extension unit	usable as thermostat extension unit

### Use

Differentiation characteristic 1 - Sales	with labelling fields
Differentiation characteristic 3 - Sales	with integral bus coupling unit

### Safety

Protection	with dismantling protection
------------	-----------------------------

### Use conditions

Operating temperature	-5...45 °C
-----------------------	------------

### Identification

Application, usage	KNX - operating systems
Product family	product family: push-button
Main design line	KNX - Berker Q.1/Q.3
Secondary design line(s)	Berker Q.3 ; Berker Q.7 ; Berker Q.1

### Instructions

Information text	Labelling field sheet, order no. 9498 31 03, available separately.
------------------	--