



75143850



**Touch sensor, 3-gang comf, intg bus coupling unit, KNX - R.3, glass p. white**

**Technical properties**

**Functions**

With room temperature controller	Yes
Function	for switch, push-button, dimmer and shutter functions ; Blocking function for sensor surface e.g. for cleaning the glass surface

**Compatibility**

Extension unit	extension unit for light scene push-button
----------------	--

**Controls and indicators**

With LED indication	Yes
Number of buttons	0
Operation	operation by gently touching the sensor surfaces on the white LED

**Dimensions**

Depth	23 mm
Height	152 mm
Width	81 mm

**Power**

Current consumption	12.5 mA
---------------------	---------

**Measurement**

Value transmitter	value transmitter for dimming, position, brightness and temperature values 1 and 2 byte
-------------------	---

**Screen**

With display	No
--------------	----

**Materials**

Colour of design line	glass polar white
RAL colour	RAL 9010 - Pure white
Surface appearance	glossy

**LED control**

LED	with blue operation LED and 6 white status LEDs
-----	---

**Installation, mounting**

Installation mode	for vertical mounting
-------------------	-----------------------

**Connection**

Bus coupling unit	with integral bus coupling unit
-------------------	---------------------------------

**Scope of delivery**

Bus connection included	Yes
-------------------------	-----

**Accessories included**

Matching products	for additional products to complement the installation in matching colours/materials, refer to the Design platform R.1/R.3 ; for suitable frames in the same "style" for additional applications, see the Design line R.x
-------------------	---

**Equipment**

Number of actuation points	6
----------------------------	---

With anti-theft/dismantling protection	Yes
--	-----

Type of configuration	Laserdruck
-----------------------	------------

**Use**

Differentiation characteristic 3 - Sales	with integral bus coupling unit
--	---------------------------------

**Safety**

REACH conform	Yes
---------------	-----

RoHS conform	Yes
--------------	-----

**Use conditions**

Operating temperature	-5...45 °C
-----------------------	------------

Temperature	temperature measurement via internal temperature sensor or external communication object ; integrated temperature sensor for operation as controller extension unit ; additional connection for external temperature sensor
-------------	---

**Identification**

Application, usage	KNX - operating systems
--------------------	-------------------------

Main design line	KNX - Berker R.3
------------------	------------------

Secondary design line(s)	KNX ; Berker R.3
--------------------------	------------------