




75161385

IP20



Technical properties

Architecture

Fixing mode	flush-mounting
-------------	----------------

Functions

With room temperature controller	No
----------------------------------	----

Function	for switch, push-button, dimmer and shutter functions
----------	-------------------------------------------------------

Compatibility

Extension unit	extension unit for light scene push-button
----------------	--------------------------------------------

Controls and indicators

With LED indication	Yes
---------------------	-----

Number of buttons	1
-------------------	---

Connectivity

Radio	for radio wall-transmitter insert
-------	-----------------------------------

Dimensions

Labelling field length (W x H)	52.3 mm
--------------------------------	---------

Height	55.4 mm
--------	---------

Width	55.4 mm
-------	---------

Measurement

Value transmitter	dimming / position value transmitter 1 byte
-------------------	---------------------------------------------

Screen

With display	No
--------------	----

Materials

Colour of labelling	217,217,217
---------------------	-------------

Colour of design line	aluminium/anthracite
-----------------------	----------------------

Colour independent of design lines	for anthracite and aluminium
------------------------------------	------------------------------

Colour	aluminium/anthracite
--------	----------------------

Material for printing	Paper
-----------------------	-------

Type of surface treatment	untreated
---------------------------	-----------

Material family	Plastic
-----------------	---------

LED control

LED	with 2 red transmission and battery status LEDs
-----	-------------------------------------------------

LED - KNX	with white operation LED and 2 red status LEDs
-----------	------------------------------------------------

Connection	
Bus coupling unit	for bus coupling unit flush-mounted
Scope of delivery	
Bus connection included	No
Equipment	
Number of actuation points	2
With anti-theft/dismantling protection	Yes
Type of configuration	Beschriftungsfeld(er) - Folie
Product type:	product type: push-button 1gang
Use	
Differentiation characteristic 1 - Sales	with labelling field
Differentiation characteristic 3 - Sales	with horizontal operation
Safety	
Protection index IP	IP20
Protection	with dismantling protection
Use conditions	
Operating temperature	-5...45 °C
Identification	
Application, usage	Radio bus - operating systems ; KNX - operating systems
Product family	product family: push-button
Secondary design line(s)	KNX ; Radio bus ; Berker S.1 ; Berker B.3 ; Berker B.7