




75161385



IP20



Technical properties

Functions

| | |
|----------------------------------|---|
| With room temperature controller | No |
| Function | for switch, push-button, dimmer and shutter functions |

Compatibility

| | |
|----------------|--|
| Extension unit | extension unit for light scene push-button |
|----------------|--|

Controls and indicators

| | |
|---------------------|-----|
| With LED indication | Yes |
| Number of buttons | 1 |

Connectivity

| | |
|-------|-----------------------------------|
| Radio | for radio wall-transmitter insert |
|-------|-----------------------------------|

Dimensions

| | |
|--------------------------------|---------|
| Labelling field length (W x H) | 52.3 mm |
| Height | 55.4 mm |
| Width | 55.4 mm |

Measurement

| | |
|-------------------|---|
| Value transmitter | dimming / position value transmitter 1 byte |
|-------------------|---|

Screen

| | |
|--------------|----|
| With display | No |
|--------------|----|

Materials

| | |
|------------------------------------|------------------------------|
| Colour of labelling | 217,217,217 |
| Colour of design line | aluminium/anthracite |
| Colour independent of design lines | for anthracite and aluminium |
| Material for printing | Paper |
| Surface appearance | glossy |
| Type of surface treatment | untreated |
| Material family | Plastic |

LED control

| | |
|-----------|---|
| LED | with 2 red transmission and battery status LEDs |
| LED - KNX | with white operation LED and 2 red status LEDs |

Connection

| | |
|-------------------|-------------------------------------|
| Bus coupling unit | for bus coupling unit flush-mounted |
|-------------------|-------------------------------------|

Scope of delivery

| | |
|-------------------------|----|
| Bus connection included | No |
|-------------------------|----|

Equipment

| | |
|----------------------------|---|
| Number of actuation points | 2 |
|----------------------------|---|

| | |
|--|-----|
| With anti-theft/dismantling protection | Yes |
|--|-----|

| | |
|-----------------------|-------------------------------|
| Type of configuration | Beschriftungsfeld(er) - Folie |
|-----------------------|-------------------------------|

| | |
|---------------|---------------------------------|
| Product type: | product type: push-button 1gang |
|---------------|---------------------------------|

Use

| | |
|--|----------------------|
| Differentiation characteristic 1 - Sales | with labelling field |
|--|----------------------|

| | |
|--|---------------------------|
| Differentiation characteristic 3 - Sales | with horizontal operation |
|--|---------------------------|

Safety

| | |
|------------|-----------------------------|
| Protection | with dismantling protection |
|------------|-----------------------------|

Use conditions

| | |
|-----------------------|------------|
| Operating temperature | -5...45 °C |
|-----------------------|------------|

Identification

| | |
|--------------------|---|
| Application, usage | Radio bus - operating systems ; KNX - operating systems |
|--------------------|---|

| | |
|----------------|-----------------------------|
| Product family | product family: push-button |
|----------------|-----------------------------|

| | |
|--------------------------|--|
| Secondary design line(s) | KNX ; Radio bus ; Berker S.1 ; Berker B.3 ; Berker B.7 |
|--------------------------|--|