



75161593

IP20

B.IQ push-button 1gan	g comf, KNX - B	3.IQ, stainless st	eel, metal brushed
-----------------------	-----------------	--------------------	--------------------

Technical properties

Architecture		
Fixing mode	flush-mounting	
Functions		
With room temperature controller	No	
Function	for switch, push-button, dimmer and shutter functions	
Compatibility		
Extension unit	extension unit for light scene push-button	
Controls and indicators		
With LED indication	Yes	
Number of buttons	1	
Operation	activation of second user level via object, one push- button operation for switching, pushing, shutters and dimming	
Dimensions		
Assembling height	16.7 mm	
Height	88.5 mm	
Width	88.5 mm	
Measurement		
Value transmitter	value transmitter for dimming, position, brightness and temperature values 1 and 2 byte	
Screen		
With display	No	
Materials		
Colour of design line	Stainless steel	
Colour	stainless steel	
RAL colour	RAL 9022 - Pearl light grey	
Material / workmanship	metal brushed	
Material	stainless steel	
Surface appearance	matt	
Type of surface treatment	brushed	
LED control		

with blue operation LED and 2 white status LEDs

(labelling field illumination)

LED

Connection		
Bus coupling unit	for bus coupling unit flush-mounted	
Settings		
Supported configuration modes	system, PB	
Parameterisation	single and two push-button operation parameteris- able	
Scope of delivery		
Bus connection included	No	
Accessories included		
Box	for installation in single standard wall boxes	
Matching products	for additional products to complement the installa- tion in matching colours/materials, refer to the Design platform S.1/B.x, for stainless steel frames in the same "style" for additional applications, see the Design line B.7	
Equipment		
Number of actuation points	2	
With anti-theft/dismantling protection	Yes	
Product type:	product type: B.IQ	
Safety		
Protection index IP	IP20	
REACH conform	Yes	
RoHS conform	Yes	
Protection	with dismantling protection	
Alarm	alarm telegram after disconnection from bus coup- ling unit 1 bit or 1 byte	
Use conditions		
Operating temperature	-545 °C	
Identification		
Application, usage	KNX - operating systems	
Product family	product family: push-button	
Main design line	KNX - Berker B.IQ	

KNX, Berker B.IQ

Secondary design line(s)