

Yes



75161593



B.IQ push-button 1gang comf, KNX - B.IQ, stainless steel, metal brushed

Technical properties

No
for switch, push-button, dimmer and shutter func-

Compatibility	
Extension unit	extension unit for light scene push-button

Controls and indicators

With LED indication

Number of buttons	1
	activation of second user level via object ; one push-
	button operation for switching, pushing, shutters and
Operation	dimmina

Dimensions

Assembling height	16.7 mm
Height	88.5 mm
Width	88.5 mm

Measurement

	value transmitter for dimming, position, brightness
Value transmitter	and temperature values 1 and 2 byte

Screen

With display	No
--------------	----

Materials

Colour of design line	Stainless steel
Material / workmanship	metal brushed
Surface appearance	matt

LED control

	with blue operation LED and 2 white status LEDs
LED	(labelling field illumination)

Connection

Bus coupling unit	for bus coupling unit flush-mounted
-------------------	-------------------------------------

Settings

Supported configuration modes	system. PB
Jupported Corniquiation modes	373(6111, 1 D

single and two push-button operation parameteris-

Scope of delivery	
Bus connection included	No
Accessories included	
Вох	for installation in single standard wall boxes
Matching products	for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x; for stainless steel frames in the same "style" for additional applications, see the Design line B.7
Equipment	
Number of actuation points	2
With anti-theft/dismantling protection	Yes
Product type:	product type: B.IQ
Safety	
REACH conform	Yes
RoHS conform	Yes
Protection	with dismantling protection
Alarm	alarm telegram after disconnection from bus coup- ling unit 1 bit or 1 byte
Use conditions	
Operating temperature	-545 °C
Identification	
Application, usage	KNX - operating systems
Product family	product family: push-button

KNX - Berker B.IQ

KNX ; Berker B.IQ

Main design line

Secondary design line(s)