




75161689



Technical properties

Functions

With room temperature controller	No
Function	for switch, push-button, dimmer and shutter functions

Compatibility

Extension unit	extension unit for light scene push-button
----------------	--

Controls and indicators

With LED indication	Yes
Number of buttons	1
Operation	one push-button operation for switching, pushing, shutters and dimming ; activation of second user level via object

Measurement

Value transmitter	value transmitter for dimming, position, brightness and temperature values 1 and 2 byte
-------------------	---

Screen

With display	No
--------------	----

Materials

Colour of design line	polar white
RAL colour	RAL 9010 - Pure white
Surface appearance	matt
Material family	Plastic

LED control

LED	with green operation LED and 2 red status LEDs
-----	--

Connection

Bus coupling unit	for bus coupling unit flush-mounted
-------------------	-------------------------------------

Settings

Parameterisation	parameterisable per channel: feedback status and brightness value, locking, scenes, soft on and off
------------------	---

Scope of delivery

Bus connection included	No
-------------------------	----

Equipment

Number of actuation points	2
With anti-theft/dismantling protection	Yes

Product type:

product type: push-button 1gang

Use

Differentiation characteristic 1 - Sales

with labelling field

Differentiation characteristic 3 - Sales

with vertical operation

Safety

Protection

with dismantling protection

Alarm

alarm telegram after disconnection from bus coupling unit 1 bit or 1 byte

Use conditions

Operating temperature

-5...45 °C

Identification

Application, usage

KNX - operating systems

Product family

product family: push-button

Secondary design line(s)

KNX ; Berker S.1 ; Berker B.3 ; Berker B.7