
Product data sheet 75161773





75161773



Technical properties

Technical properties	
Functions	
With room temperature controller	No
Function	for switch, push-button, dimmer and shutter func- tions
Compatibility	
Extension unit	extension unit for light scene push-button
Controls and indicators	
With LED indication	Yes
Number of buttons	1
Operation	activation of second user level via object ; one push- button operation for switching, pushing, shutters and dimming
Dimensions Labelling field length (W x H)	66.8 x 52.8 mm
Height	52.8 mm
Width	
Measurement	
Value transmitter	value transmitter for dimming, position, brightness and temperature values 1 and 2 byte
Screen	
With display	No
Materials	
Colour of labelling	105,105,105
Colour of design line	stainless steel
Colour independent of design lines	stainless steel
Material for printing	Paper
Surface appearance	glossy
Material family	Plastic
LED control	
LED	with white operation LED and 2 red status LEDs
Connection	
Bus coupling unit	for bus coupling unit flush-mounted
Settings	

Parameterisation

single and two push-button operation parameteris-

able

Scope of delivery

Bus connection included	No
Equipment	
Number of actuation points	2
With anti-theft/dismantling protection	Yes
Type of configuration	Beschriftungsfeld(er) - Folie
Product type:	product type: push-button 1gang
Use	
Differentiation characteristic 1 - Sales	with labelling field
Differentiation characteristic 3 - Sales	with horizontal operation
Safety	
Protection	with dismantling protection
	with dismantling protection alarm telegram after disconnection from bus coup- ling unit 1 bit or 1 byte
Alarm	alarm telegram after disconnection from bus coup-
Alarm Use conditions	alarm telegram after disconnection from bus coup- ling unit 1 bit or 1 byte
Alarm Use conditions Operating temperature	alarm telegram after disconnection from bus coup- ling unit 1 bit or 1 byte
Alarm Use conditions Operating temperature Identification	alarm telegram after disconnection from bus coup- ling unit 1 bit or 1 byte -545 °C
Alarm Use conditions Operating temperature Identification Application, usage	alarm telegram after disconnection from bus coup- ling unit 1 bit or 1 byte -545 °C KNX - operating systems
Protection Alarm Use conditions Operating temperature Identification Application, usage Product family Main design line	alarm telegram after disconnection from bus coup-