


75161773



## Technical properties

### Architecture

Fixing mode	flush-mounting
-------------	----------------

### Functions

With room temperature controller	No
----------------------------------	----

Function	for switch, push-button, dimmer and shutter functions
----------	---

### Compatibility

Extension unit	extension unit for light scene push-button
----------------	--

### Controls and indicators

With LED indication	Yes
---------------------	-----

Number of buttons	1
-------------------	---

Operation	activation of second user level via object, one push-button operation for switching, pushing, shutters and dimming
-----------	--

### Dimensions

Labelling field length (W x H)	66.8 x 52.8 mm
--------------------------------	----------------

Height	52.8 mm
--------	---------

Width	66.8 mm
-------	---------

### Measurement

Value transmitter	value transmitter for dimming, position, brightness and temperature values 1 and 2 byte
-------------------	---

### Screen

With display	No
--------------	----

### Materials

Colour of design line	stainless steel
-----------------------	-----------------

Colour independent of design lines	stainless steel
------------------------------------	-----------------

Colour	Stainless steel
--------	-----------------

RAL colour	RAL 9022 - Pearl light grey
------------	-----------------------------

Material	thermoplastic
----------	---------------

Material for printing	Paper
-----------------------	-------

Type of surface treatment	Painted
---------------------------	---------

Material family	Plastic
-----------------	---------

### LED control

LED	with white operation LED and 2 red status LEDs
-----	--

<b>Connection</b>	
Bus coupling unit	for bus coupling unit flush-mounted
<b>Settings</b>	
Parameterisation	single and two push-button operation parameterisable
<b>Scope of delivery</b>	
Bus connection included	No
<b>Equipment</b>	
Number of actuation points	2
With anti-theft/dismantling protection	Yes
Type of configuration	Beschriftungsfeld(er) - Folie
Product type:	product type: push-button 1gang
<b>Use</b>	
Differentiation characteristic 1 - Sales	with labelling field
Differentiation characteristic 3 - Sales	with horizontal operation
<b>Safety</b>	
Protection index IP	IP20
Protection	with dismantling protection
Alarm	alarm telegram after disconnection from bus coupling unit 1 bit or 1 byte
<b>Use conditions</b>	
Operating temperature	-5...45 °C
<b>Identification</b>	
Application, usage	KNX - operating systems
Product family	product family: push-button
Main design line	KNX - Berker K.5
Secondary design line(s)	Berker K.5, KNX