



75162373



Technical properties

recinical properties	
Architecture	
Fixing mode	flush-mounting
Functions	
With room temperature controller	No
Function	for switch, push-button, dimmer and shutter functions
Compatibility	
Extension unit	extension unit for light scene push-button
Controls and indicators	
With LED indication	Yes
Number of buttons	2
Dimensions	
Labelling field length (W x H)	66.8 x 25 mm
Height	55.1 mm
Width	70.5 mm
Measurement	
Value transmitter	dimming / position value transmitter 1 byte
Screen	
With display	No
Materials	
Colour of labelling	105,105,105
Colour of design line	stainless steel
Colour	stainless steel
Material for printing	Paper
Surface appearance	matt
Type of surface treatment	Painted
Material family	Plastic
LED control	
LED - KNX	with white operation LED and 4 red status LEDs
Connection	
Bus coupling unit	for bus coupling unit flush-mounted

Scope of delivery

Bus connection included No **Equipment** Number of actuation points 4 With anti-theft/dismantling protection Yes Type of configuration Beschriftungsfeld(er) - Folie Product type: product type: push-button 2gang Use Differentiation characteristic 1 - Sales with labelling fields Differentiation characteristic 3 - Sales with horizontal operation Safety Protection index IP IP20 Protection with dismantling protection **Use conditions** -5...45 °C Operating temperature Identification KNX - operating systems ; Radio bus - operating

systems

product family: push-button

KNX; Radio bus; Berker K.5

Application, usage

Secondary design line(s)

Product family