

system, PB



75162592

IP20

B.IQ push-button 2gang comf, KNX - B.IQ, glass black

Technical properties

Et 1	
Fixing mode	flush-mounting
Functions	
With room temperature controller	No
Function	for switch, push-button, dimmer and shutter func- tions
Compatibility	
Extension unit	extension unit for light scene push-button
Controls and indicators	
With LED indication	Yes
Number of buttons	2
Operation	activation of second user level via object ; one push- button operation for switching, pushing, shutters and dimming
Dimensions	
Assembling height	16.7 mm
Height	88.5 mm
Width	88.5 mm
Measurement	
Value transmitter	value transmitter for dimming, position, brightness and temperature values 1 and 2 byte
Screen	
With display	No
Materials	
Colour of design line	glass black
Colour	black
Type of surface treatment	Painted
LED control	
LED	with blue operation LED and 4 white status LEDs (labelling field illumination)
Connection	
Bus coupling unit	for bus coupling unit flush-mounted
Settings	

Supported configuration modes

Parameterisation	single and two push-button operation parameterisable
Scope of delivery	
Bus connection included	No
Accessories included	
Вох	for installation in single standard wall boxes
Matching products	for glass frames in the same "style" for additional applications, see the Design line B.7; for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x
Equipment	
Number of actuation points	4
With anti-theft/dismantling protection	Yes
Product type:	product type: B.IQ
Safety	
Protection index IP	IP20
REACH conform	Yes
RoHS conform	Yes
Protection	with dismantling protection
Alarm	alarm telegram after disconnection from bus coupling unit 1 bit or 1 byte
Use conditions	
Operating temperature	-545 °C
Identification	
Application, usage	KNX - operating systems
Product family	product family: push-button
Main design line	KNX - Berker B.IQ
Secondary design line(s)	KNX ; Berker B.IQ