



75162599



IP20

## B.IQ push-button 2gang comf, KNX - B.IQ, p. white, matt, plastic

### Technical properties

#### Functions

With room temperature controller No

Function for switch, push-button, dimmer and shutter functions

#### Compatibility

Extension unit extension unit for light scene push-button

#### Controls and indicators

With LED indication Yes

Number of buttons 2

Operation activation of second user level via object ; one push-button operation for switching, pushing, shutters and dimming

#### Dimensions

Height 88.5 mm

Width 88.5 mm

#### Measurement

Value transmitter value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

#### Screen

With display No

#### Materials

Colour of labelling 105,105,105

Colour of design line polar white

RAL colour RAL 9010 - Pure white

Surface appearance matt

Type of surface treatment untreated

#### LED control

LED with blue operation LED and 4 white status LEDs (labelling field illumination)

#### Connection

Bus coupling unit for bus coupling unit flush-mounted

#### Settings

Supported configuration modes system, PB

Parameterisation single and two push-button operation parameterisable

**Scope of delivery**

Bus connection included	No
-------------------------	----

**Accessories included**

Box	for installation in single standard wall boxes
-----	--

Matching products

for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x ; for plastic frames in the same "style" for additional applications, see the Design line B.7

**Equipment**

Number of actuation points	4
----------------------------	---

With anti-theft/dismantling protection	Yes
--	-----

Type of configuration	Laserdruck
-----------------------	------------

Product type:	product type: B.IQ
---------------	--------------------

**Safety**

REACH conform	Yes
---------------	-----

RoHS conform	Yes
--------------	-----

Protection	with dismantling protection
------------	-----------------------------

Alarm

alarm telegram after disconnection from bus coupling unit 1 bit or 1 byte

**Use conditions**

Operating temperature	-5...45 °C
-----------------------	------------

**Identification**

Application, usage	KNX - operating systems
--------------------	-------------------------

Product family	product family: push-button
----------------	-----------------------------

Main design line	KNX - Berker B.IQ
------------------	-------------------

Secondary design line(s)	KNX ; Berker B.IQ
--------------------------	-------------------