





75162683



IP20



## Technical properties

### Functions

With room temperature controller No

Function for switch, push-button, dimmer and shutter functions

### Compatibility

Extension unit extension unit for light scene push-button

### Controls and indicators

With LED indication Yes

Number of buttons 2

Operation one push-button operation for switching, pushing, shutters and dimming ; activation of second user level via object

### Measurement

Value transmitter value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

### Screen

With display No

### Materials

Colour of design line aluminium

Material / workmanship lacquered

Surface appearance matt

Material family Plastic

### LED control

LED with green operation LED and 4 red status LEDs

### Connection

Bus coupling unit for bus coupling unit flush-mounted

### Settings

Parameterisation single and two push-button operation parameterisable

### Scope of delivery

Bus connection included No

### Equipment

Number of actuation points 4

With anti-theft/dismantling protection Yes

Product type:

product type: push-button 2gang

---

**Use**

Differentiation characteristic 1 - Sales

with labelling field

Differentiation characteristic 3 - Sales

with vertical operation

---

**Safety**

Protection

with dismantling protection

Alarm

alarm telegram after disconnection from bus coupling unit 1 bit or 1 byte

---

**Use conditions**

Operating temperature

-5...45 °C

---

**Identification**

Application, usage

KNX - operating systems

Product family

product family: push-button

Secondary design line(s)

KNX ; Berker S.1 ; Berker B.3 ; Berker B.7