

Yes



75162685









Technical properties

| Functions | |
|--|--|
| With room temperature controller | No |
| Function | for switch, push-button, dimmer and shutter func- tions |
| Compatibility | |
| Extension unit | extension unit for light scene push-buttor |
| Controls and indicators | |
| With LED indication | Yes |
| Number of buttons | 2 |
| Operation | one push-button operation for switching, pushing shutters and dimming ; activation of second user level via object |
| Measurement | |
| Value transmitter | value transmitter for dimming, position, brightness and temperature values 1 and 2 byte |
| Screen | |
| With display | No |
| Materials | |
| Colour of design line | anthracite |
| Surface appearance | mati |
| Type of surface treatment | untreated |
| Material family | Plastic |
| LED control | |
| LED | with green operation LED and 4 red status LEDs |
| Connection | |
| Bus coupling unit | for bus coupling unit flush-mounted |
| Settings | |
| Parameterisation | single and two push-button operation parameteris able |
| Scope of delivery | |
| Bus connection included | No |
| Equipment | |
| Number of actuation points | 4 |
| With anti-thoft/diamontling protection | V- |

With anti-theft/dismantling protection

| Product type: | product type: push-button 2gang |
|--|---|
| Use | |
| Differentiation characteristic 1 - Sales | with labelling field |
| Differentiation characteristic 3 - Sales | with vertical operation |
| Safety | |
| Protection | with dismantling protection |
| Alarm | alarm telegram after disconnection from bus coupling unit 1 bit or 1 byte |
| Use conditions | |
| Operating temperature | -545 °C |
| Identification | |
| Application, usage | KNX - operating systems |
| Product family | product family: push-button |
| Secondary design line(s) | KNX ; Berker S.1 ; Berker B.3 ; Berker B.7 |