





75162689



IP20



## Technical properties

### Functions

With room temperature controller No

Function for switch, push-button, dimmer and shutter functions

### Compatibility

Extension unit extension unit for light scene push-button

### Controls and indicators

With LED indication Yes

Number of buttons 2

Operation one push-button operation for switching, pushing, shutters and dimming ; activation of second user level via object

### Measurement

Value transmitter value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

### Screen

With display No

### Materials

Colour of design line polar white

RAL colour RAL 9010 - Pure white

Surface appearance matt

Type of surface treatment untreated

Material family Plastic

### LED control

LED with green operation LED and 4 red status LEDs

### Connection

Bus coupling unit for bus coupling unit flush-mounted

### Settings

Parameterisation single and two push-button operation parameterisable

### Scope of delivery

Bus connection included No

### Equipment

Number of actuation points 4

With anti-theft/dismantling protection	Yes
Product type:	product type: push-button 2gang
<b>Use</b>	
Differentiation characteristic 1 - Sales	with labelling field
Differentiation characteristic 3 - Sales	with vertical operation
<b>Safety</b>	
Protection	with dismantling protection
Alarm	alarm telegram after disconnection from bus coupling unit 1 bit or 1 byte
<b>Use conditions</b>	
Operating temperature	-5...45 °C
<b>Identification</b>	
Application, usage	KNX - operating systems
Product family	product family: push-button
Secondary design line(s)	KNX ; Berker S.1 ; Berker B.3 ; Berker B.7