

Yes



75162780







Berker S.1/B.3/B.7 Push Button 2-gang, Comfort with Label, White and Polar White

Technical properties

Function	าร
----------	----

With room temperature controller	No
Function	for switch, push-button, dimmer and shutter func- tions

Compatibility

Extension unit	extension unit for light scene push-button
----------------	--

Controls and indicators

With LED indication

Number of buttons	2
	one push-button operation for switching, pushing,
	shutters and dimming; activation of second user
Operation	level via object

Dimensions

Labelling field length (W x H)	52.3 x 24.9 mm
Height	55.4 mm
Width	55.6 mm

Measurement

	value transmitter for dimming, position, brightness
Value transmitter	and temperature values 1 and 2 byte

Screen

With display	No
--------------	----

Materials

Colour of labelling	105,105,105
Colour independent of design lines	for white and polar white
Colour	white
Material for printing	Paper

Surface appearance	glossy
Type of surface treatment	untreated

LED control

LEDs

Connection

Bus coupling unit	for bus coupling unit flush-mounted

Settings

Parameterisation	single and two push-button operation parameteris- able
Scope of delivery	
Bus connection included	No
Equipment	
Number of actuation points	4
With anti-theft/dismantling protection	Yes
Type of configuration	Beschriftungsfeld(er) - Folie
Product type:	product type: push-button 2gang
Use	
Differentiation characteristic 1 - Sales	with labelling fields
Differentiation characteristic 3 - Sales	with horizontal operation
Safety	
Protection	with dismantling protection
Alarm	alarm telegram after disconnection from bus coup- ling unit 1 bit or 1 byte
Use conditions	
Operating temperature	-545 °C
Identification	
Application, usage	KNX - operating systems
Product family	product family: push-button
Main design line	KNX - Berker S.1/B.3/B.7
Secondary design line(s)	Berker B.1 ; KNX ; Berker S.1 ; Berker B.3 ; Berker B.7