75163785

Berker S.1/B.3/B.7 Push Button 3-gang, Comfort with Label, Anthracite/Aluminium

Technical properties

Functions

With room temperature controller	No
Function	for switch, push-button, dimmer and shutter functions

Compatibility

Extension unit	extension unit for light scene push-button

Controls and indicators

With LED indication	Yes
Number of buttons	3
Operation	one push-button operation for switching, pushing, shutters and dimming ; activation of second user level via object

Dimensions

Labelling field length (W x H)	52.3 x 15.6 mm
Height	55.4 mm
Width	55.6 mm

Measurement

Value transmitter	value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

Screen

With display	No

Materials

Colour of labelling	217,217,217
Colour of design line	aluminium/anthracite
Colour independent of design lines	for anthracite and aluminium
Material for printing	Paper
Surface appearance	glossy
Type of surface treatment	untreated
Material family	Plastic

LED control

LED	with white operation LED and 6 red status LEDs

Connection

Bus coupling unit	for bus coupling unit flush-mounted

Settings

Subject to technical modifications

Parameterisation	single and two push-button operation parameterisable

Scope of delivery

Bus connection included	No

Equipment

Number of actuation points	6
With anti-theft/dismantling protection	Yes
Type of configuration	Beschriftungsfeld(er) - Folie
Product type:	product type: push-button 3gang

Use

Differentiation characteristic 1 - Sales	with labelling fields
Differentiation characteristic 3 - Sales	with horizontal operation

Safety

Protection	with dismantling protection
Alarm	alarm telegram after disconnection from bus coupling unit 1 bit or 1 byte

Use conditions

Operating temperature	-5…45 °C

Identification

Application, usage	KNX - operating systems
Product family	product family: push-button
Secondary design line(s)	KNX ; Berker S.1 ; Berker B.3 ; Berker B.7