

75164094



B.IQ push-button 4gang, KNX - B.IQ, al., al. anodised

## **Technical properties**

With room temperature controller	N
Function	for switch, push-button, dimmer and shutter func tion
Compatibility	
Extension unit	extension unit for light scene push-butto
Controls and indicators	
With LED indication	Ye
Number of buttons	
Dimensions	
Assembling height	16.7 mr
Height	118.1 mn
Width	88.5 mr
Measurement	
Value transmitter	dimming / position value transmitter 1 byte
Screen	
With display	N
Materials	
Colour of design line	Aluminiur
	aluminium, anodise
Material / workmanship	
	mat
Surface appearance	
Surface appearance	
Surface appearance Material family LED control	Meta
Surface appearance Material family LED control	Meta
Material / workmanship Surface appearance Material family LED control LED Gonnection Bus coupling unit	Meta with blue operation LED and 8 white status LED
Surface appearance Material family LED control LED Connection	mat Meta with blue operation LED and 8 white status LED for bus coupling unit flush-mounter

Box

for installation in single standard wall boxes

for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x ; for aluminium frames in the same "style" for additional applications, see the Design line B.7

## Equipment

Number of actuation points	8
With anti-theft/dismantling protection	Yes
Product type:	product type: B.IQ
Safety	
REACH conform	Yes
RoHS conform	Yes
Protection	with dismantling protection
Use conditions	
Operating temperature	-545 °C
Identification	
Application, usage	KNX - operating systems
Product family	product family: push-button
Main design line	KNX - Berker B.IQ
Secondary design line(s)	KNX ; Berker B.IC