



75164591

Technical properties

Architecture

Fixing mode	flush-mounting
-------------	----------------

Functions

With room temperature controller	No
----------------------------------	----

Function	for switch, push-button, dimmer and shutter functions
----------	---

Compatibility

Extension unit	extension unit for light scene push-button
----------------	--

Controls and indicators

With LED indication	Yes
---------------------	-----

Number of buttons	4
-------------------	---

Operation	second operating level via object or 3-button handle ; lockable via 3-button actuation ; one push-button operation for switching, pushing, shutters and dimming
-----------	---

Dimensions

Height	118.1 mm
--------	----------

Width	88.5 mm
-------	---------

Measurement

Value transmitter	value transmitter for dimming, position, brightness and temperature values 1 and 2 byte
-------------------	---

Screen

With display	No
--------------	----

Materials

Colour of design line	glass polar white
-----------------------	-------------------

Colour	polarwhite
--------	------------

Type of surface treatment	Painted
---------------------------	---------

LED control

LED	with blue operation LED and 8 white status LEDs (labelling field illumination)
-----	--

Connection

Bus coupling unit	for bus coupling unit flush-mounted
-------------------	-------------------------------------

Settings

Supported configuration modes	system, PB
-------------------------------	------------

Parameterisation

single and two push-button operation parameterisable

Scope of delivery

Bus connection included

No

Accessories included

Box

for installation in single standard wall boxes

Matching products

for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x ; for glass frames in the same "style" for additional applications, see the Design line B.7

Equipment

Number of actuation points

8

With anti-theft/dismantling protection

Yes

Product type:

product type: B.IQ

Safety

Protection index IP

IP20

Protection

with dismantling protection

Alarm

alarm telegram after disconnection from bus coupling unit 1 bit or 1 byte

Use conditions

Operating temperature

-5...45 °C

Identification

Application, usage

KNX - operating systems

Product family

product family: push-button

Main design line

KNX - Berker B.IQ

Secondary design line(s)

KNX ; Berker B.IQ