





75164685



IP20



Technical properties

Functions

With room temperature controller No

Function for switch, push-button, dimmer and shutter functions

Compatibility

Extension unit extension unit for light scene push-button

Controls and indicators

With LED indication Yes

Number of buttons 4

Operation one push-button operation for switching, pushing, shutters and dimming ; lockable via 3-button actuation ; second operating level via object or 3-button handle

Measurement

Value transmitter value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

Screen

With display No

Materials

Colour of design line anthracite

Surface appearance matt

Type of surface treatment untreated

Material family Plastic

LED control

LED with green operation LED and 8 red status LEDs

Connection

Bus coupling unit for bus coupling unit flush-mounted

Settings

Parameterisation single and two push-button operation parameterisable

Scope of delivery

Bus connection included No

Equipment

Number of actuation points 8

With anti-theft/dismantling protection Yes

Product type:

product type: push-button 4gang

Use

Differentiation characteristic 1 - Sales

with labelling field

Differentiation characteristic 3 - Sales

with vertical operation

Safety

Protection

with dismantling protection

Alarm

alarm telegram after disconnection from bus coupling unit 1 bit or 1 byte

Use conditions

Operating temperature

-5...45 °C

Identification

Application, usage

KNX - operating systems

Product family

product family: push-button

Secondary design line(s)

KNX ; Berker S.1 ; Berker B.3 ; Berker B.7