




75164770



## Technical properties

### Functions

With room temperature controller No

Function for switch, push-button, dimmer and shutter functions

### Compatibility

Extension unit extension unit for light scene push-button

### Controls and indicators

With LED indication Yes

Number of buttons 4

Operation second operating level via object or 3-button handle ; one push-button operation for switching, pushing, shutters and dimming ; lockable via 3-button actuation

### Dimensions

Labelling field length (W x H) 66.8 x 25 mm

Height 111.1 mm

Width 70.5 mm

### Measurement

Value transmitter value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

### Screen

With display No

### Materials

Colour of labelling 105,105,105

Colour of design line polar white

RAL colour RAL 9010 - Pure white

Material for printing Paper

Surface appearance glossy

Type of surface treatment untreated

Material family Plastic

### LED control

LED with white operation LED and 8 red status LEDs

### Connection

Bus coupling unit for bus coupling unit flush-mounted

### Settings

**Scope of delivery**

Bus connection included	No
-------------------------	----

**Equipment**

Number of actuation points	8
----------------------------	---

With anti-theft/dismantling protection	Yes
--	-----

Type of configuration	Beschriftungsfeld(er) - Folie
-----------------------	-------------------------------

Product type:	product type: push-button 4gang
---------------	---------------------------------

**Use**

Differentiation characteristic 1 - Sales	with labelling fields
--	-----------------------

Differentiation characteristic 3 - Sales	with horizontal operation
--	---------------------------

**Safety**

Protection	with dismantling protection
------------	-----------------------------

Alarm	alarm telegram after disconnection from bus coupling unit 1 bit or 1 byte
-------	---

**Use conditions**

Operating temperature	-5...45 °C
-----------------------	------------

Storage/transport temperature	-20...70 °C (storage at > 45°C reduces the service life)
-------------------------------	--

**Identification**

Application, usage	KNX - operating systems
--------------------	-------------------------

Product family	product family: push-button
----------------	-----------------------------

Secondary design line(s)	Berker K.1 ; KNX
--------------------------	------------------

**Instructions**

Special note text	Use only in combination with frame frame with large cut-out.
-------------------	--