

105,105,105











Technical properties

 :	
Inctions	

With room temperature controller	No
Function	for switch, push-button, dimmer and shutter functions

Compatibility

Extension unit	extension unit for light scene push-button
----------------	--

Controls and indicators

Number of buttons	4
With LED indication	Yes

second operating level via object or 3-button handle ; one push-button operation for switching, pushing, shutters and dimming; lockable via 3-button actuation

Dimensions

Operation

Labelling field length (W x H)	66.8 x 25 mm
Height	111.1 mm
Width	70.5 mm

Measurement

	value transmitter for dimming, position, brig	ntness
Value transmitter	and temperature values 1 and	2 byte

Screen

With display	No
--------------	----

Materials

Colour of labelling

Colour of design line	polar white
RAL colour	RAL 9010 - Pure white
Material for printing	Paper
Surface appearance	glossy

Type of surface treatment untreated

Material family Plastic

LED control

LED with white operation LED and 8 red status LEDs

Connection

Bus coupling unit for bus coupling unit flush-mounted

Settings

No

Scope of delivery

Bus connection included

Equipment

 Number of actuation points
 8

 With anti-theft/dismantling protection
 Yes

 Type of configuration
 Beschriftungsfeld(er) - Folie

 Product type:
 product type: push-button 4gang

Use

Differentiation characteristic 1 - Sales with labelling fields

Differentiation characteristic 3 - Sales with horizontal operation

Safety

Protection with dismantling protection

alarm telegram after disconnection from bus coupling unit 1 bit or 1 byte

Use conditions

Operating temperature -5...45 °C -20...70 °C (storage at > 45°C reduces the service Storage/transport temperature

Identification

Application, usage KNX - operating systems

Product family product family: push-button

Secondary design line(s) Berker K.1; KNX

Instructions

 $\begin{tabular}{lll} Use only in combination with frame frame with large \\ Special note text & cut-out. \end{tabular}$