



75164773



Technical properties

Functions

With room temperature controller No

Function for switch, push-button, dimmer and shutter functions

Compatibility

Extension unit extension unit for light scene push-button

Controls and indicators

With LED indication Yes

Number of buttons 4

Operation lockable via 3-button actuation ; one push-button operation for switching, pushing, shutters and dimming ; second operating level via object or 3-button handle

Dimensions

Labelling field length (W x H) 66.8 x 25 mm

Height 111.1 mm

Width 70.5 mm

Measurement

Value transmitter value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

Screen

With display No

Materials

Colour of labelling 105,105,105

Colour of design line stainless steel

Material for printing Paper

Surface appearance glossy

Type of surface treatment untreated

Material family Plastic

LED control

LED with white operation LED and 8 red status LEDs

Connection

Bus coupling unit for bus coupling unit flush-mounted

Settings

Scope of delivery

Bus connection included	No
-------------------------	----

Equipment

Number of actuation points	8
----------------------------	---

With anti-theft/dismantling protection	Yes
----------------------------------------	-----

Type of configuration	Beschriftungsfeld(er) - Folie
-----------------------	-------------------------------

Product type:	product type: push-button 4gang
---------------	---------------------------------

Use

Differentiation characteristic 1 - Sales	with labelling fields
------------------------------------------	-----------------------

Differentiation characteristic 3 - Sales	with horizontal operation
------------------------------------------	---------------------------

Safety

Protection	with dismantling protection
------------	-----------------------------

Alarm	alarm telegram after disconnection from bus coupling unit 1 bit or 1 byte
-------	---------------------------------------------------------------------------

Use conditions

Operating temperature	-5...45 °C
-----------------------	------------

Storage/transport temperature	-20...70 °C (storage at > 45°C reduces the service life)
-------------------------------	----------------------------------------------------------

Identification

Application, usage	KNX - operating systems
--------------------	-------------------------

Product family	product family: push-button
----------------	-----------------------------

Secondary design line(s)	KNX ; Berker K.5
--------------------------	------------------

Instructions

Special note text	Use only in combination with frame frame with large cut-out.
-------------------	--------------------------------------------------------------