







Technical properties

With room temperature controller	No
Function	for switch, push-button, dimmer and shutter func- tions
Compatibility	
Extension unit	extension unit for light scene push-buttor
Controls and indicators	
With LED indication	Yes
Number of buttons	4
Operation Dimensions	lockable via 3-button actuation ; one push-button operation for switching, pushing, shutters and dimming ; second operating level via object or 3- button handle
Labelling field length (W x H)	66.8 x 25 mm
Height	111.1 mm
Width	70.5 mm
Measurement	
Value transmitter	value transmitter for dimming, position, brightness and temperature values 1 and 2 byte
Screen	
With display	Nc
Materials	
Colour of labelling	105,105,105
Colour of design line	stainless stee
Material for printing	Paper
Surface appearance	glossy
Type of surface treatment	untreated
Material family	Plastic
LED control	
LED	with white operation LED and 8 red status LED
Connection	
Bus coupling unit	for bus coupling unit flush-mounted

Settings

single and two push-button operation parameterisable

Parameterisation

Bus connection included	No
Equipment	
Number of actuation points	8
With anti-theft/dismantling protection	Yes
Type of configuration	Beschriftungsfeld(er) - Folie
Product type:	product type: push-button 4gang
Use	
Differentiation characteristic 1 - Sales	with labelling fields
Differentiation characteristic 3 - Sales	with horizontal operation
Safety	
Protection	with dismantling protection
Alarm	alarm telegram after disconnection from bus coup- ling unit 1 bit or 1 byte
Use conditions	
Operating temperature	-545 °C
Storage/transport temperature	-2070 °C (storage at > 45°C reduces the service life)
Identification	
Application, usage	KNX - operating systems
Product family	product family: push-buttor
Secondary design line(s)	KNX ; Berker K.S
Instructions	
Special note text	Use only in combination with frame frame with large cut-out