



75261626



KNX cont. comf 2.2 m, KNX - Q.1/Q.3, ant. velvety, lacq.

Technical properties

Architecture

Fixing mode	flush-mounting
-------------	----------------

Functions

Max. temporisation	306 h
--------------------	-------

Potentiometer for additional delay time	± 50 %
---	--------

Function	Functions for lighting operating mode: Switching, Value transmitter and Light scene call, parameter defineable lock function
----------	--

Slide switch	with slide switch for OFF/automatic/ON
--------------	--

Compatibility

Extension unit	also suitable as extension unit
----------------	---------------------------------

Controls and indicators

Number of switching segments	72
------------------------------	----

Dimensions

Dimensions assembling height	23.5 mm
------------------------------	---------

Nominal mounting height	2.2 m
-------------------------	-------

Optimum mounting height	2.2 m
-------------------------	-------

Power

Power consumption, KNX	≈ 110 mW
------------------------	----------

Measurement

Detection field, semi-oval shaped	≈ 12 x 12 m
-----------------------------------	-------------

Reach distance

Range, frontal	≈ 12 m
----------------	--------

Range, frontal (at 1.1 m installation height)	≈ 6 m
---	-------

Range, side	each ≈ 6 m
-------------	------------

Range, side (at 1.1 m installation height)	each ≈ 3 m
--	------------

Max. transmission range frontally	12 m
-----------------------------------	------

Max. transmission range sideways	6 m
----------------------------------	-----

Cover, door

Cover	with cover to limit detection angle to 90°
-------	--

Detection

Number of detection levels	2
----------------------------	---

Detection angle	180 °
-----------------	-------

Detection angle vertical	0 / 7 °
Detection angle horizontal	0 / 180 °
Sensor type	detector of movement

Materials

Colour of design line	anthracite
RAL colour	RAL 7021 - Black grey
Material / workmanship	lacquered
Material	thermoplastic
Surface appearance	velvety

Lighting control

Response brightness, configurable	3...100 lx / daytime operation
-----------------------------------	--------------------------------

LED control

LED	with red diagnostic LED for brightness-independent walk test function and disassembly message
-----	---

Incandescent bulbs control

Max. power with incandescent lamps	0 W
------------------------------------	-----

Connection

Bus coupling unit	for bus coupling unit flush-mounted
-------------------	-------------------------------------

Settings

Supported configuration modes	system
Response brightness adjustable by potentiometer	± 50 %
Response sensitivity, settable	20...100 %
Min. temporisation	130 ms
Delay time	≈ 10 s
Additional delay time programmable	130 ms...306 h
Setting	with potentiometers for fine adjustment of the response brightness, sensitivity and delay time

Equipment

Product type:	product type: movement
Lighting	with lighting and message mode

Safety

Protection index IP	IP20
Alarm	alarm telegram after disconnection from bus coupling unit, 1-bit

Use conditions

Operating temperature	-5...45 °C
-----------------------	------------

Identification

Application, usage	KNX - sensors
Product family	product family: physical sensors
Main design line	KNX - Berker Q.1/Q.3
Secondary design line(s)	Berker Q.1, KNX, Berker Q.3, Motion detector

Instructions

Information text

Application as for order no. 7526 15 .. Caution:
Direct sunlight can lead to false alarms when using
alarm application. Avoid using detection field equip-
ment on windows.