

stainless steel



75662773





Push-button 2gang with room thermostat, display, K.5, stainless steel

Colour of design line

LED

Connection

Technical properties	
Architecture	
Fixing mode	flush-mounting
Functions	
With room temperature controller	Yes
Timers	with room temperature timer
Compatibility	
Extension unit	extension unit for light scene push-button
Controls and indicators	
With LED indication	Yes
Number of buttons	2
Operation	one push-button operation for switching, pushing, shutters and dimming
Dimensions	
Labelling field length (W x H)	66.8 x 15.7 mm
Height	55.1 mm
Width	70.9 mm
Measurement	
Value transmitter	value transmitter for dimming, position, brightness and temperature values 1 and 2 byte
Screen	
With display	Yes
Materials	

Colour	stainless steel
RAL colour	RAL 9022 - Pearl light grey
Material	thermoplastic
Material for printing	Paper
Surface appearance	matt

Surface appearance	matt
Type of surface treatment	Painted
Material family	Plastic

LED control

with white operation LED and 4 red status LEDs

Settings

single and two push-button operation parameteris-Parameterisation able

Scope of delivery

Bus connection included No

Accessories included

Box for installation in single standard wall boxes

Equipment

Number of actuation points 6

With anti-theft/dismantling protection Yes

Type of configuration Beschriftungsfeld(er) - Folie

Product type: product type: push-button 2gang

Control for individual single room temperature control

Software

Update with flash-controller technology

Safety

Protection index IP IP20
Protection with dismantling protection

alarm telegram after disconnection from bus coupling unit 1 bit or 1 byte

Use conditions

Operating temperature -5...45 °C
Energy efficiency class IV (2%)

Identification

Application, usage KNX - operating systems

Product family product family: push-button

Main design line KNX - Berker K.1/K.5

Secondary design line(s) KNX, Berker K.5