



75664593



## B.IQ push-b. 4gang thermostat, display, KNX - B.IQ, stainl. steel metal brushed

### Technical properties

#### Functions

With room temperature controller	Yes
Function	with valve protection function
Timers	with room temperature timer and 2-week timer functions

#### Compatibility

Extension unit	extension unit for light scene push-button
----------------	--

#### Controls and indicators

With LED indication	Yes
Number of buttons	4
Operation	one push-button operation for switching, pushing, shutters and dimming

#### Dimensions

Assembling height	16.7 mm
Width of rail mounted device (RMD)	0 modules
Height	149.2 mm
Width	88.5 mm

#### Measurement

Value transmitter	value transmitter for dimming, position, brightness and temperature values 1 and 2 byte
-------------------	---

#### Screen

With display	Yes
--------------	-----

#### Materials

Colour of design line	Stainless steel
RAL colour	RAL 9022 - Pearl light grey
Material / workmanship	metal brushed
Material	stainless steel
Surface appearance	matt
Material family	Metal

#### LED control

LED	with blue operation LED and 8 white status LEDs (labelling field illumination)
-----	--

#### Settings

Parameterisation	single and two push-button operation parameterisable
------------------	--

**Accessories included**

---

Box	for installation in single standard wall boxes
-----	--

---

Matching products	for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x, for stainless steel frames in the same "style" for additional applications, see the Design line B.7
-------------------	---

**Equipment**

---

Number of actuation points	10
----------------------------	----

---

Product type:	product type: B.IQ
---------------	--------------------

---

Control	for individual single room temperature control
---------	--

---

**Software**

---

Update	with flash-controller technology
--------	----------------------------------

---

**Safety**

---

Protection	with dismantling protection
------------	-----------------------------

---

**Use conditions**

---

Operating temperature	-5...45 °C
-----------------------	------------

---

Energy efficiency class	IV (2%)
-------------------------	---------

---

**Identification**

---

Application, usage	KNX - operating systems
--------------------	-------------------------

---

Product family	product family: push-button
----------------	-----------------------------

---

Release issue	2.6
---------------	-----

---

Main design line	KNX - Berker B.IQ
------------------	-------------------

---

Secondary design line(s)	KNX, Berker B.IQ
--------------------------	------------------

---