75665599

B.IQ push-button 5gang thermostat, display, KNX - B.IQ, p. white, matt, plastic

Technical properties

Functions

With room temperature controller	Yes
Function	with valve protection function
Timers	with room temperature timer and 2-week timer functions

Compatibility

Extension unit	extension unit for light scene push-button

Controls and indicators

With LED indication	Yes
Number of buttons	5
Operation	one push-button operation for switching, pushing, shutters and dimming

Dimensions

Width of rail mounted device (RMD)	0 modules
Height	178.8 mm
Width	88.5 mm

Measurement

Value transmitter	value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

Screen

With display	Yes

Materials

Colour of design line	polar white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	matt
Material family	Plastic

Settings

Parameterisation	single and two push-button operation parameterisable

Scope of delivery

Bus connection included	No

Accessories included

Box	for installation in single standard wall boxes

Subject to technical modifications

Matching products	for plastic frames in the same "style" for additional applications, see the Design line B.7, for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x

Equipment

Type of configuration	Laserdruck
Product type:	product type: B.IQ
Control	for individual single room temperature control

Software

Update	with flash-controller technology

Safety

Protection	with dismantling protection

Use conditions

Operating temperature	-5...45 °C
Energy efficiency class	IV (2%)

Identification

Application, usage	KNX - operating systems
Product family	product family: push-button
Release issue	2.6
Main design line	KNX - Berker B.IQ
Secondary design line(s)	Berker B.IQ, KNX