



80960226

IP20



Cover for 1gang for push-button module, clearlens, Q.x, ant. velvety, lacq.

### Technical properties

#### Functions

	operating concept "independent push-button" function predefined ; operating concept for "roller shutter/blind" function predefined ; switching of scenes (1..8) possible ; brightness value of the status LED for day/nighttime operation preset, change-over for day/nighttime operation possible ; integrated temperature sensor with output of the measured values ; Colour of status LED uniformly adjustable for complete device ; push-button functions: including switching, dimming, roller shutter/blind, timer, priority, operating mode changeover
Easy link functions	

Function	Function for manual interruption of automatic functions already triggered
----------	---

Function	operating surfaces as buttons (single-surface operation) and rockers (two-surface operation) ; the brightness of status LEDs are individually adjustable for button/ rocker function ; brightness value of the status LEDs for day/nighttime operation adjustable via object or manually ; value transmitter for dimming, position, brightness temperature values 1 and 2 byte ; integrated temperature sensor with output of the measured values via object ; parameter defineable lock function ; button/rocker functions for switching, dimming, roller shutter/blind, value transmitter 1/2 byte, room thermostat extension unit, priority, scene, automatic control deactivation
----------	---

#### Controls and indicators

Operation	operating areas configurable as one or two-area operation
Button / push-button	with programming button and red programming LED

#### Voltage

Operating voltage over bus	21...32 V DC
----------------------------	--------------

#### Dimensions

Height	58 mm
--------	-------

#### Power

Power consumption, KNX	≈ 108 mW
------------------------	----------

#### Camera

Lens	with clear lens for RGB status display of the push-button module
------	--

#### Materials

Colour of design line	anthracite
Material / workmanship	lacquered
Surface appearance	velvety

**Connection**

Bus coupling unit	with integral bus coupling unit
Bus connection	bus connection via connecting terminal

**Settings**

Supported configuration modes	system, easy
-------------------------------	--------------

**Equipment**

Buzzer/siren	with integrated buzzer for acoustic identification of the device within the system
--------------	--

**Use**

Differentiation characteristic 2 - Sales	with clear lens
--	-----------------

**Safety**

REACH conform	Yes
RoHS conform	Yes
Halogen free	No
Protection	with dismantling protection

**Use conditions**

Operating temperature	-5...45 °C
Storage/transport temperature	-20...70 °C (storage at > 45°C reduces the service life)
Temperature	integrated temperature sensor with output of the measured values via object

**Identification**

Application, usage	KNX - operating systems
Product family	product family: push-button
Main design line	KNX - Berker Q.1/Q.3
Secondary design line(s)	KNX ; Berker Q.1 ; Berker Q.3 ; Berker Q.7 ; Berker Q.9