




EE850



IP55

**Motion detector comfort 140°, IP55, wall mounted, white**

**Technical properties**

**Architecture**

Fixing mode surface-mounting

**Main electrical features**

Rated operational voltage Ue 230 V

Frequency 50/60 Hz

**Dimensions**

Height of installed product 2.5 mm

Recommended installation height 2.5 m

**Reach distance**

Range, side each ≈ 6 m

**Power supply**

Supply voltage 230 V +10% / -15%

**Detection**

Detection angle 140 °

Detection angle 140 °

Frontal detecting distance 16 m

Side detecting distance 10 m

**Materials**

Colour white

RAL colour RAL 9010 - Pure white

Material plastic

**Lighting control**

Response brightness, adjustable ≈ 5...1000 lx

Brightness measurement range 5 / 1000 Lux

**Installation, mounting**

Maximum Mounting Height 4 m

**Connection**

Type of connection with screw terminals

**Settings**

Response value sensitivity adjustable Yes

Delay time, adjustable 5 s...30 mn

**Scope of delivery**

---

Component	with fitting material
-----------	-----------------------

**Equipment**

---

Remote controllable	EE806
Angle of horizontal detection	140 °
Slewing	vertically slewing and horizontally rotating

**Safety**

---

Protection index IP	IP55
---------------------	------

**Use conditions**

---

Operating temperature	-20...55 °C
Storage/transport temperature	-20...60 °C

**Identification**

---

Application, usage	Motion detector
Main design line	Motion detectors