




EE850



IP55

Motion detector comfort 140°, IP55, wall mounted, white

Technical properties

Architecture

Bus system Without

Functions

Function Presence simulation ; can be used as a single unit, main device or extension unit

Main electrical features

Rated operational voltage Ue 230 V

Frequency 50/60 Hz

Dimensions

Height of installed product 2.5 mm

Recommended installation height 2.5 m

Reach distance

Range, side each ≈ 6 m

Power supply

Supply voltage 230 V +10% / -15%

Detection

Detection angle 140 °

Detection angle 140 °

Frontal detecting distance 16 m

Side detecting distance 10 m

Materials

Colour white

RAL colour RAL 9010 - Pure white

Material plastic

Lighting control

Response brightness, adjustable ≈ 5...1000 lx

Brightness measurement range 5 / 1000 Lux

LED control

230V LED lamps 20 x 20 W

LED with LED detection and mode indicator

Installation, mounting

Maximum Mounting Height 4 m

Connection

Type of connection	with screw terminals
--------------------	----------------------

Settings

Response value sensitivity adjustable	Yes
---------------------------------------	-----

Delay time, adjustable	5 s...30 mn
------------------------	-------------

Setting	with potentiometers for setting the response brightness and delay time without dismantling
---------	--

Scope of delivery

Component	with fitting material
-----------	-----------------------

Equipment

Remote controllable	EE806
---------------------	-------

Angle of horizontal detection	140 °
-------------------------------	-------

Slewing	vertically slewing and horizontally rotating
---------	--

Safety

REACH conform	Yes
---------------	-----

RoHS conform	Yes
--------------	-----

Use conditions

Operating temperature	-20...55 °C
-----------------------	-------------

Storage/transport temperature	-20...60 °C
-------------------------------	-------------

Energy-saving	low intrinsic energy requirement ; energy saving by means of presence and brightness-dependent ON and OFF switching of light
---------------	--

Identification

Application, usage	Motion detector
--------------------	-----------------

Main design line	Motion detectors
------------------	------------------