



EVN002



IP20

Remote Control Dimmer universal 500W

Technical properties

Architecture

Type of order Push button

Configuration

Number of modules 2

Main electrical features

Rated operational voltage U_e 230 V

Frequency 50/60 Hz

Voltage

Operating voltage 230 V~ +10%/-15%

Fuse

Fuse with electronic short-circuit and overload protection

Dimensions

Depth of installed product 62 mm

Height of installed product 85 mm

Installation height 0 / 1000 m

Width of installed product 35 mm

Width of rail mounted device (RMD) 2 modules

Length

Max distance to switches 50 mm

Power

Dimmable conventional transformers 500 VA

Halogen switching capacity 230V 500 W

Power consumed 4.5 W

Power consumption (operation) 4.5 W

Power consumption (standby) 0.2 W

Incandescent bulb power 500 W

Total power loss under IN 0.2 W

Conventional transformers 500 VA

Electronic transformers 500 W

Cover, door

Surface cover Other

Materials

Surface appearance

matt

Fluorescent bulbs control

Dimmable energy-saving lamps	100 W
Lighting power fluocompact lamps with built-in ballast	100 W

LED control

Quantity of dimmable, 230 V retrofit LED lamps	10
Max number of LED/CFL lamps	10
Dimmable 230 V LED lamps	100 W
Power LED	100 W

Incandescent bulbs control

Max. power with incandescent lamps	500 W
230 V incandescent lamps and halogen lamps	500 W

Installation, mounting

Fixing type	With claws
Mounting type	din-Rail
Installation mode	for mounting on DIN rail

Connection

Connection cross-sect. flexible conductor	1,5 / 6mm ²
Connection cross-sect. rigid cable	1,5 / 6mm ²
Type of load	universal
Conductor cross-section (flexible)	1.5...6 mm ²
Conductor cross-section (rigid)	1.5...6 mm ²
Type of connection	with screw terminals
Connection	Connection for non-illuminated push-buttons
Type of connection	with screw

Cable

Load cable length	50 m
-------------------	------

Equipment

Type of dimmer	No
Dimming principle	automatic load detection

Safety

REACH conform	No
RoHS conform	Yes
Halogen free	No

Use conditions

Operating temperature	-20...50 °C
Storage/transport temperature	-20...50 °C

Instructions

Information text	Only for use with dimmable lamps!
------------------	-----------------------------------