



MZ201



## Auxiliary contact 1C+10 6A 240V AC

## **Technical properties**

Δ	rc	hi	it	PC	tı.	ıre

Fixing made	Cli
Fixing mode	Clipped
Configuration	
Number of modules	0.5
Main electrical features	
Rated operational voltage Ue	230 / 415 V
Type of supply voltage	AC
Voltage	
Rated insulation voltage	4000 V
Max operating voltage	240 V
Rated operational voltage in DC	12 / 250 V
Electric current	
Acceptable current rating with AC1	6 A
Rated current	6 A
Imin=f(U=12V DC) for power circuit	0.3 A
Imin = f (U = 230 V DC)	0.6 A
Imin=f(U=400V AC) for power circuit	3 A
Dimensions	
Depth of installed product	40 mm
Height of installed product	80 mm
Width of installed product	9.5 mm
Power	
Total power loss under IN	0.1 W
Endurance	
Electric endurance in number of cycles	6000
Number of mechanical operations	12000
Installation, mounting	
Tightening torque	1,2Nm
Factory fitted	No
Connection	
Connection cross-sect. flexible conductor	6mm²
Connection cross-sect. rigid cable	10mm²

Type of contacts	1NC+1NO
Type of connection	with screw
Equipment	
Quantity of NC contacts	1
Quantity of NO contacts	1
Quantity of INV contacts	0
Safety	
REACH conform	Yes
RoHS conform	Yes
Halogen free	No
Use conditions	
Operating temperature	-2560 °C
Air humidity protection	95% / 80°C
Storage/transport temperature	-4080 °C
Identification	
Aesthetic for B.G. Protection devices	FD